

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Amendments to the Claims:

This listing of the claims will replace all prior versions, and listings, of the claims in the application.

Listing of the Claims:

Claims 1-2 (canceled)

Claim 3 (currently amended): The system of claim 1 19

wherein the sequential readout circuit determines a difference between a final integration light value and a reset value for each photocell in a time sequential manner.

Claim 4 (currently amended): The system of claim 1 19 wherein the array includes a plurality of columns; wherein the system further includes

a sample and hold circuit for each column; wherein each sample and hold circuit samples and holds ~~the~~ a voltage value of a photocell that is disposed in the respective column; wherein each sample and hold circuit includes

a single sampling capacitor, and

a single transistor coupled to the single sampling capacitor.

Claim 5 (currently amended): The system of claim + 19 ~~wherein the sequential readout circuit includes an amplifier that includes a first input; an output; and~~ further comprising:

an integration capacitor having a first electrode for coupling to the ~~first~~ input of the single amplifier and a second electrode for coupling to the output of the single amplifier; wherein the single amplifier includes a charge transfer mode and a unity gain mode.

Claim 6 (currently amended): The system of claim + 19 wherein the sequential readout circuit includes

a level shifting circuit coupled to the ~~first~~ input and the output of the single amplifier for performing level shifting of the output of the single amplifier.

Claim 7 (currently amended): The system of claim + 19 wherein the sequential readout circuit includes

a gain manipulation circuit coupled to the ~~first~~ input and the output of the single amplifier for performing gain manipulation of the single amplifier.

Claim 8 (currently amended): The system of claim 4 19 wherein each photocell includes

a photodiode for detecting light and responsive thereto for generating a voltage representation thereof; wherein the photodiode includes an integration node;

a first transistor coupled to the photodiode for resetting the integration node in response to a reset signal;

a second transistor coupled to the integration node for shifting the level of the voltage at the integration node; and

a third transistor coupled to the second transistor for reading out the level-shifted voltage in response to a read signal.

Claim 9 (currently amended): The system of claim 4 19 wherein the system is implemented in one of a scanner application, an optical mouse application, a video game controller application, a movement encoder application, a near field application, and a far field application.

Claim 10 (currently amended): A sequential readout circuit for coupling to an array of photocells; wherein the array includes at least a first row, a first column, a second column, a first photocell that is disposed in the first row and the first column, and a second photocell that is disposed in the first row and in the second column, the sequential readout circuit comprising:

- a) ~~an~~ a single amplifier for reading out ~~the~~ a value of the photocells in the array one photocell at a time;
- b) a first switch for selectively coupling the amplifier to the first column; and
- c) a second switch for selectively coupling the amplifier to the second column.

Claim 11 (original): The sequential readout circuit of claim 10

wherein the single amplifier determines the difference between a reset voltage (V_{reset}) and a light voltage (V_{light}) for the first photocell and the second photocell in a time sequential manner.

Claim 12 (original): The sequential readout circuit of claim 10 further comprising:

a sample and hold circuit for each column; wherein each sample and hold circuit samples and holds the voltage value of a photocell that is disposed in the respective column.

Claim 13 (currently amended): The sequential readout circuit of claim 12 wherein each sample and hold circuit includes

- a sampling capacitor, and
- a transistor coupled to the ~~first~~ sampling capacitor.

Claim 14 (original): The sequential readout circuit of claim 10

wherein the amplifier includes a charge transfer mode, a unity gain mode, a first input; and an output; and

wherein the circuit further includes an integration capacitor having a first electrode for coupling to the first input and a second electrode for coupling to the output of the amplifier.

Claim 15 (original): The sequential readout circuit of claim 10 further comprising:

a level-shifting mechanism coupled to the amplifier for performing level shifting of the output of the amplifier.

Claim 16 (original): The sequential readout circuit of claim 10 further comprising:

a gain mechanism coupled to the amplifier for performing gain manipulation of the amplifier.

Claim 17 (original): The sequential readout circuit of claim 10 wherein each photocell includes

a photodiode for detecting light and responsive thereto for generating a voltage representation thereof; wherein the photodiode includes an integration node;

a first transistor coupled to the photodiode for resetting the integration node in response to a reset signal;
a second transistor coupled to the integration node for shifting the level of the voltage at the integration node; and
a third transistor coupled to the second transistor for reading out the level-shifted voltage in response to a read signal.

Claim 18 (original): The sequential readout circuit of claim 10 wherein the sequential readout circuit is implemented in one of a scanner application, an optical mouse application, a video game controller application, a movement encoder application, a near field application, and a far field application.

Claim 19 (new): A system comprising:

- a) an array of photocells that are arranged in rows and columns;
and
- b) a sequential readout circuit for sequentially reading out the value of the photocells one photocell at a time; wherein the sequential readout circuit includes a single amplifier that includes an input for coupling to one column of the array of photocells at a time and an output for generating a voltage value corresponding to a photocell.